CLEANING PROCESS SMALL BORE RIFLE

PRECISION ENGINEERING

RHAKAR -

1 Unlatch the bolt and remove it from the receiver.

Z Insert a cleaning rod guide into the receiver.





FOR WINNERS!









Is your rifle properly unloaded?







Follow the cleaning instructions and you will always be successful!












www.bleiker.ch



Apply a VFG felt pellet onto the cleaning rod adaptor and push it through the barrel to the muzzle. Remove the soiled felt pellet and pull back the cleaning rod.

4 Apply a new VFG felt pellet onto the cleaning rod adaptor and moisten the pellet with Rimfire Blend. Insert the moistened felt pellet into the barrel and push it with short back and forth movements to the muzzle. Remove the soiled VFG and pull back the cleaning rod.

5 Intensive cleaning with the brush. After each shooting, the barrel has to be cleaned with a bronze brush. Push the brush in the direction of the muzzle. Repeat this three to five times. After the muzzle exit, remove the brush from the cleaning rod. Only a bronze brush can completely remove lead remnants.

6 Apply a new VFG felt pellet and push it through the barrel to the muzzle. Repeat this until the felt pellets are no longer soiled.

7 Apply a new felt pellet and moisten it with gun oil. Insert the oil-moistened felt pellet into the barrel and push it in to the muzzle with short movements.

Remove the cleaning rod guide and clean the action system of the receiver with a cotton bud.

Clean the bolt with a cloth and gun oil. Apply a slight film of gun oil to the bolt, the lock nuts and the cam.

10 Insert the bolt into the receiver and close it. You have to be able to close the bolt without feeling any resistance. In the case that you feel some resistance, remove the bolt from the receiver and check whether the action system contains any impurities or foreign particles.

